

# Water Analysis

NANOCOLOR® Heating Blocks



## Heating blocks of the future

### **NANOCOLOR® VARIO 4 and VARIO C2**

- Touch screen with intuitive user guidance
- Lockable protective lids for maximum safety
- USB interfaces for state-of-the-art PC connection
- COD, *total-N* and *total-P* in just 30 minutes
- Internal quality control according to ISO 9001

**MACHEREY-NAGEL**

[www.mn-net.com](http://www.mn-net.com)



Since 1911

# NANOCOLOR® Heating Blocks

## Save time

### Intuitive operation

- Convenient input via icons
- Quick and easy selection of heating programs



Start screen



Temperature selection



Time selection



Program start



### Time-saving procedures

- Extremely short warm-up times (from 20 to 160 °C in just 10 minutes)
- High-speed COD, *total*-Nitrogen, *total*-Phosphorous and *total*-Metals in just 30 minutes



### Self-explanatory user guidance

- User-friendly, bright touch screen
- Operation without time-consuming training

## Experience flexibility



### The ideal size for any purpose

NANOCOLOR® VARIO C2: simultaneous digestion of up to 12 samples

NANOCOLOR® VARIO 4: simultaneous digestion of up to 24 samples in two individually controlled heating units for a higher sample throughput




### Standard programs and easy programming

- 5 pre-programmed temperatures 70 / 100 / 120 / 148 / 160 °C
- 4 pre-programmed heating times 30 min / 60 min / 120 min / cont.
- 7 free memory locations between 40 -160 °C (1 °C increments)
- 8 free memory locations between 0h:01min – 9h:59min (1min increments)

### Suitable for all NANOCOLOR® digestion methods

Application	Temperature	Time
COD (DIN ISO 15705)	148 °C	120 min
High-speed COD	160 °C	30 min
TOC	120 °C	120 min
<i>total</i> -Nitrogen	120 °C	30 min
<i>total</i> -Phosphorous	120 °C	30 min
Organic acids	100 °C	10 min
<i>total</i> -Metals (Cadmium, Chromate, Iron, Cobalt, Copper, Nickel, Zinc)	120 °C	30 min
AOX	120 °C	30 min
Hydrocarbons	148 °C	120 min
Programmable, user-defined programs	40 – 160 °C	0h:01min – 9h:59min

## Be safe



### Constant digestion conditions

- High temperature stability
- Electronic overheating protection
- Graphic display of heating curves



### Maximum safety for the user

- Extra strong safety covers as contact protection (10 mm, replaceable) on the heating block surface
- Lockable protective lids
- Display alert in case of open protective lid



## Meet specifications

### Internal quality control according to ISO 9001

- In conformance with requirements of internal quality control (IQC)
- Comply with demands of supervisors and authorities
- Heating curves to check temperature stability
- Electronic temperature control and fully automatic calibration with the NANOCOLOR® T-Set (REF 919 917)
- Comfortable data transfer via USB or serial interface RS 232
- Easy generation of quality certificates in accordance to GLP with the NANOCOLOR® T-Set software



### NANOCOLOR® T-Set

#### Automatic temperature control and calibration of the heating blocks

- Connect the RS 232 plug of the T-Set to the heating block
- Place the temperature sensor into the small bore located on the safety cover



Select „T-Set“ in the menu





Select the respective program



Start the program

### Universal thermometer for external temperature measurements

- Connect the RS 232 plug of the T-Set to the heating block
- Dip the temperature sensor into the respective sample solution
- The temperature is displayed in the heating block's display



# NANOCOLOR® Heating blocks

## Technical Data



<b>Instrument:</b>	<b>NANOCOLOR® VARIO 4</b>	<b>NANOCOLOR® VARIO C2</b>
<b>Type:</b>	Programmable heating blocks for chemical-analytical digestions with 24 or 12 holes / for test tubes with 16 mm OD (outer diameter) / integrated protective lids	
<b>Display:</b>	Coloured, backlit LCD touch screen	
<b>Operation:</b>	Display menu guidance via touch screen	
<b>Temperatures:</b>	5 pre-programmed temperatures: 70 / 100 / 120 / 148 / 160 °C 7 free memory locations for individual temperature settings	
<b>Temperature range:</b>	40 – 160 °C (1 °C increments)	
<b>Temperature stability:</b>	± 1 °C (according to DIN, EN, ISO and EPA methods)	
<b>Warm-up time:</b>	from 20 °C to 160 °C within 10 minutes	
<b>Heating times:</b>	4 preprogrammed heating times: 30 min / 60 min / 120 min / cont. 8 free memory locations for individual heating times	
<b>Time range:</b>	0h:01min – 9h:59min (increments 0h:01min)	
<b>Safety:</b>	Replaceable safety covers as contact protection Lockable protective lids Overheating protection	
<b>Interfaces:</b>	Bidirectional serial RS 232, USB A (master) and USB B (slave)	
<b>Analytical quality control:</b>	With NANOCOLOR® T-Set (REF 919 917) optional fully automatic calibration and preparation of test certificates for instrument control and monitoring according to ISO 9001)	
<b>Update:</b>	Via internet and USB stick	
<b>Power supply:</b>	110 – 230 V ~, 50/60 Hz	
<b>Power consumption:</b>	250 / 500 VA	125 / 250 VA
<b>Dimensions (B x T x H):</b>	290 x 287 x 146 mm	169 x 282 x 146 mm
<b>Weight:</b>	approx. 3.2 kg	approx. 2.0 kg
<b>Marking:</b>	CE	
<b>Warranty:</b>	2 years	



These instruments conform to the following directives:  
- 2006/95/EC – Low-Voltage Directive  
- 004/108/EC - EMV Directive

### Ordering information:

#### **NANOCOLOR® VARIO 4**

Heating block incl. 2 protective lids, power line cord, USB cable, software-DVD, certificate and manual

**REF 919 300**

#### **NANOCOLOR® VARIO C2**

Heating block incl. protective lid, power line cord, USB cable, software-DVD, certificate and manual

**REF 919 350**

#### **NANOCOLOR® T-Set**

Electronic temperature sensor incl. software-DVD, certificate and manual

**REF 919 917**

Your local distributor

[www.mn-net.com](http://www.mn-net.com)

## MACHEREY-NAGEL



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6-8 · D-52355 Düren · Germany

Germany

and international:

Tel.: +49 (0) 24 21 96 90

Fax: +49 (0) 24 21 96 91 99

E-mail: [info@mn-net.com](mailto:info@mn-net.com)

Switzerland:

MACHEREY-NAGEL AG

Tel.: +41 (0) 62 388 55 00

Fax: +41 (0) 62 388 55 05

E-mail: [sales-ch@mn-net.com](mailto:sales-ch@mn-net.com)

France:

MACHEREY-NAGEL EUROL

Tel.: +33 (0) 3 88 68 22 68

Fax: +33 (0) 3 88 51 76 88

E-mail: [sales-fr@mn-net.com](mailto:sales-fr@mn-net.com)



Since 1911